MT-170

Technical Data Sheet

SPECIFICATIONS	
Color	Colorless
Density	0.800 – 0.920 g/cm^3
Volatiles	100%

Characteristics

It is a colorless liquid with a characteristics and volatile odor.

Uses

Specially formulated as a solvent for the series:

- SUBALOX U.
- SUBALOX PC 1090-Z.
- For urethane nature products.

Storage Conditions

Closed containers, under roof and a temperature under 104ºF (40ºC) under 80% relative humidity.

Handling Safety

- **MT-170** solvent should be used in adequately ventilated areas. Contact with skin will cause slight irritation: so solvent-resistant neoprene gloves, safety glasses a mask should be worn and used in well-ventilated areas away from sparks and ignition sources.
- In case of accidental contact with eyes the product must be removed with plenty of water.
- In case of ingestion seek medical attention.
- **MT-170** solvent is flammable due to the vapor pressure of its solvents. The material should be stored in a cool place. When containers are opened loosen the cap slowly and carefully until there is no pressure.

Remarks

We guarantee the quality of our products according to the general sales and application guidelines, our technical use method advice, verbally expressed and written and scenarios. Where conducted as part of our research, therefore we suggest you conduct your own lab and field test. The application and the terms on how you use our products are out of the reach of our control; therefore, you are responsible for any results. For more information call our technical advisers in Mexico 55 5650 5089, 55 5650 5238 and 55 5657 2784.